

HCW607HTSXUK

12NC/Fx: F168039

GTIN (EAN) code: 5054645680399

DIMENSION	MEAS	SURE	DIMENS	
OVERALL CABINET			APPLIANC	
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm	Height of th	
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	450	mm	Width of the	
MIN Height of the base cabinet niche, including all required space for installation or ventilation	0	mm	Depth of th	
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm	Maximum o	
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	453	mm	Lateral clea	
MAX Height of the base cabinet niche, including all required space for installation or ventilation	0	mm	neighbour	
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm	Projection (
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	560	mm	Projection of	
MIN Width of the base cabinet niche, including all required space for installation or ventilation	0	mm	appliance,	
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm	When prod	
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mm	Space in fro	
MAX Width of the base cabinet niche, including all required space for installation or ventilation	0	mm	dimension	
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mm	Height from	
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	550	mm	Frontal han	
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	0	mm	Frontal han	
Space in front, which is required to install bottom trim	8	mm	MIN Height	
ndicates whether a ventilation opening is needed or not. Default is "N"	No		MAX Heigh	
WALL CABINET (vent-shaft incoming)			Width of the	
Indicates the position of the freespace for the inbound airflow (wall cabinet)	-		Depth of th	
Minimum space or inbound ventilation (wall cabinet)	0	mm	Full depth of	
Minimum area for inbound ventilation cavity (wall cabinet)	0	cm ²	Minimum h	
WALL CABINET (vent-shaft outgoing)			Maximum h	
Indicates the position of the freespace for the outbound airflow (wall cabinet)	-		Diameter m	
Minimum space or outbound ventilation (wall cabinet)	0	mm	Diameter n	
Minimum area for outbound ventilation cavity (wall cabinet)	0	cm ²	Indicates m	
TALL CABINET (vent-shaft incoming)			Projection of	
Indicates the position of the freespace for the inbound airflow (tall cabinet)	-		Height tube	
Minimum space for inbound ventilation (tall cabinet)	0	mm	Appliance of	
Minimum area for inbound ventilation cavity (tall cabinet)	0	cm ²	Appliance	
TALL CABINET (vent-shaft outgoing)			Projection of	
Indicates the position of the freespace for the outbound airflow (tall cabinet)	-		Maximum a	
Minimum space for outbound ventilation (tall cabinet)	0	mm	Appliance	
Minimum area for outbound ventilation cavity (tall cabinet)	0	cm ²	Lateral proj mounted	
BASE CABINET (vent-shaft incoming)				
Indicates the position of the freespace for the inbound airflow (base cabinet)	-		Lateral proj Maximum a	
Minimum space for inbound ventilation (base cabinet)	0	mm		
Minimum area for inbound ventilation cavity (base cabinet)	0	cm ²	Appliance	
BASE CABINET (vent-shaft outgoing)			Depth from	
Indicates the position of the freespace for the outbound airflow (base cabinet)	-		Height from	
Minimum space for outbound ventilation (base cabinet)	0	mm		
Minimum area for outbound ventilation cavity (base cabinet)	0	cm ²		

APPLIANCE		
Height of the front	455	mm
Width of the front	595	mm
Depth of the front	20	mm
Maximum depth all protruding elements, e.g. handles, controls	0	mm
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees		mm
Projection of front in relation to housing of appliance	13	mm
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable	0	mm
When product panel is missing, set to 0		mm
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension	340	mm
Height from bearing area of appliances and lower handle	344	mm
Frontal handle thickness	13	mm
Frontal handle width	0	mm
MIN Height of the product body		mm
MAX Height of the product body	442	mm
Width of the product body	559	mm
Depth of the product body	543	mm
Full depth of product excluding protruding interface elements	563	mm
Minimum height from bottom line hood to top line air outlet	0	mm
Maximum height from bottom line hood to top line air outlet	0	mm
Diameter minimum air outlet	0	mm
Diameter maximum air outlet		mm
Indicates measure between center of air outlet hole and rear wall	0	mm
Projection of the rear flap in relation to bearing area		mm
Height tube connection for air outlet	0	mm
Appliance can be used as base for other appliances from the same manufacturer. Default is "No"	No	
Appliance Flap door		
Projection of the opened flap in relation to bearing area	6	mm
Maximum angle when flap door is opened totally	85	mm
Appliance Side swing door		
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted	0	mm
Lateral projection of opened front at the side where the hinge is fixed	0	mm
Maximum angle when door is opened totally	0	mm
Appliance other		
Depth from front end of the niche to the front end of the freespace of the retrace	0	mm
Height from niche to bottom end of freespace for the retrace	0	mm