

HPM K12C XUK

12NC/Fx: F170198

GTIN (EAN) code: 5054645701988

DIMENSION	MEASURE	
OVERALL CABINET		
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	360	mm
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	360	mm
MIN Height of the base cabinet niche, including all required space for installation or ventilation	0	mm
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	363	mm
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	363	mm
MAX Height of the base cabinet niche, including all required space for installation or ventilation	0	mm
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	560	mm
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	560	mm
MIN Width of the base cabinet niche, including all required space for installation or ventilation	0	mm
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	568	mm
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mm
MAX Width of the base cabinet niche, including all required space for installation or ventilation	0	mm
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	300	mm
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	300	mm
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	0	mm
Space in front, which is required to install bottom trim	0	mm
Indicates whether a ventilation opening is needed or not. Default is "N"	No	
WALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (wall cabinet)	-	
Minimum space or inbound ventilation (wall cabinet)	0	mm
Minimum area for inbound ventilation cavity (wall cabinet)	0	cm ²
WALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (wall cabinet)	-	
Minimum space or outbound ventilation (wall cabinet)	0	mm
Minimum area for outbound ventilation cavity (wall cabinet)	0	cm ²
TALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (tall cabinet)	-	
Minimum space for inbound ventilation (tall cabinet)	0	mm
Minimum area for inbound ventilation cavity (tall cabinet)	0	cm ²
TALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (tall cabinet)	-	
Minimum space for outbound ventilation (tall cabinet)	0	mm
Minimum area for outbound ventilation cavity (tall cabinet)	0	cm²
BASE CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (base cabinet)	-	
Minimum space for inbound ventilation (base cabinet)	0	mm
Minimum area for inbound ventilation cavity (base cabinet)	0	cm ²
BASE CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (base cabinet)	-	
Minimum space for outbound ventilation (base cabinet)	0	mm
Minimum area for outbound ventilation cavity (base cabinet)	0	cm ²

DIMENSION		EASURE	
APPLIANCE			
Height of the front	382	mm	
Width of the front	595	mm	
Depth of the front	21	mm	
Maximum depth all protruding elements, e.g. handles, controls	0	mm	
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees	0	mm	
Projection of front in relation to housing of appliance	20	mm	
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable	14	mm	
When product panel is missing, set to 0	80	mm	
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension	593	mm	
Height from bearing area of appliances and lower handle	0	mm	
Frontal handle thickness	0	mm	
Frontal handle width	0	mm	
MIN Height of the product body	348	mm	
MAX Height of the product body	348	mm	
Width of the product body	544	mm	
Depth of the product body	299	mm	
Full depth of product excluding protruding interface elements	320	mm	
Minimum height from bottom line hood to top line air outlet	0	mm	
Maximum height from bottom line hood to top line air outlet	0	mm	
Diameter minimum air outlet	0	mm	
Diameter maximum air outlet	0	mm	
Indicates measure between center of air outlet hole and rear wall	0	mm	
Projection of the rear flap in relation to bearing area	0	mm	
Height tube connection for air outlet	0	mm	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No	' -		
Appliance Flap door			
Projection of the opened flap in relation to bearing area	0	mm	
Maximum angle when flap door is opened totally	0	mm	
Appliance Side swing door			
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted	0	mm	
Lateral projection of opened front at the side where the hinge is fixed	2	mm	
Maximum angle when door is opened totally	85	mm	
Appliance other			
Depth from front end of the niche to the front end of the freespace of the retrace	0	mm	
Height from niche to bottom end of freespace for the retrace	0	mm	